



PATENT
ATTORNEY DOCKET NO.: 040894-5606



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents
BOX PATENT APPLICATION
Washington, D.C. 20231

**TRANSMITTAL FOR A NEWLY EXECUTED ORIGINAL APPLICATION
UNDER 37 C.F.R. §1.53(b)**

This is a request for filing a patent application under 37 C.F.R. §1.53(b) for:

Inventor: Masahiko KUBO

For: A COLOR IMAGE PROCESSING METHOD AND A COLOR IMAGE PROCESSOR

1. This is a new ☒ **Utility** ☐ **Design** ☐ **Plant** patent application.
2. The papers enclosed to obtain a filing date are as follows:

<u>62</u>	Pages of Specification including
<u>0</u>	Title Page
<u>6</u>	Pages of Claims
<u>1</u>	Page of Abstract
<u>17</u>	Sheets of drawings containing <u>9</u> Figures

☐ The enclosed drawing(s) are photograph(s), and there is also attached a PETITION TO ACCEPT PHOTOGRAPH(S) AS DRAWING(S)
3. Combined Declaration and Power of Attorney

<input checked="" type="checkbox"/>	Enclosed and is executed by the inventor.
<input type="checkbox"/>	Not Enclosed.

This application is being filed under the provisions of 37 C.F.R. §1.53(f).
Applicant(s) await notification from the Patent and Trademark Office of the time set for filing the Declaration and paying the filing fees.

4. Language

☒ English☐ Non-English

This application is being filed in accordance with 37 C.F.R. §1.52(d) and §608.01 of the MPEP. Applicant(s) await notification from the Patent and Trademark Office of the time set for filing the verified English translation and the processing fee.

5. Assignment

☒ An assignment of the invention to Fuji Xerox Co., Ltd. and a PTO Form-1595, Recordation Form Cover Sheet, are enclosed.

☐ An assignment will be filed at a later date.

6. Priority - foreign applications under 35 U.S.C. §119(a)-(d) or §365(b) or PCT international applications under 35 U.S.C. §365(a) designating at least one country other than the U.S.

☒ Priority of the following foreign application is claimed:

Country	Application No.	Filed
Japan	11-353936	December 14, 1999

Certified copy: ☐ is attached. ☒ will follow.

7. Priority based on provisional application(s) - 35 U.S.C. §119(e)

☐ Priority of the following provisional application(s) is claimed:

Application No.	Filed

A. Relate Back - 35 U.S.C. §119(e)

- ☐ Amend the specification by inserting before the first line the sentence:
 "This application claims priority of copending provisional application(s)
 No. _____ filed on _____."

8. Small entity status

- ☐ A statement claiming small entity status under 37 C.F.R. §§1.9 and 1.27 is enclosed.

9. Fee Calculation (37 C.F.R. §1.16)

CLAIMS FOR FEE CALCULATION				
	Number Filed	Number Extra	at Rate of	Basic Fee Utility \$710.00 Design \$320.00
Total Claims (37 C.F.R. §1.16(c))	16 - 20 =	0	\$ 18.00 each=	\$0.00
Independent Claims (37 C.F.R. §1.16(b))	2 - 3 =	0	\$ 80.00 each=	\$0.00
Multiple dependent claim(s), if any (37 C.F.R. §1.16(d))			\$270.00	\$0.00
SUB-TOTAL =				\$710.00
Reduction by 1/2 for filing by a small entity				- \$
TOTAL FILING FEE =				\$710.00

10. Fee Payment

- ☐ Not Enclosed. **NO FEE IS BEING PAID BY CHECK OR DEPOSIT ACCOUNT AT THIS TIME.**
 This application is being filed under the provisions of 37 C.F.R. §1.53(f).
 Applicant(s) await notification from the Patent and Trademark Office of the time set for filing the Declaration and paying the filing fees.

[X] Enclosed.

Two checks in the amounts of \$ 710 and \$40.00 representing the basic filing fee of \$710.00 and an assignment recording fee of \$40.00 are enclosed.

11. [X] **Except** for issue fees payable under 37 C.F.R. §1.18, the Commissioner is hereby authorized by this paper to charge any additional fees during the entire pendency of this application including fees due under 37 C.F.R. §§1.16 and 1.17 which may be required, including any required extension of time fees, or credit any overpayment to Deposit Account 50-0310. This paragraph is intended to be a **CONSTRUCTIVE PETITION FOR EXTENSION OF TIME** in accordance with 37 C.F.R. §1.136(a)(3).


12. Additional papers enclosed:

- ☐ Preliminary Amendment
- ☐ Information Disclosure Statement
- ☐ Form PTO-1449, __ documents included
- ☐ Declaration of Biological Deposit
- ☐ Submission of "Sequence Listing", computer readable copy and/or amendment pertaining thereto for biotechnology invention containing nucleotide and/or amino acid sequence.

Please accord this application an application number and filing date.

Respectfully submitted,

MORGAN, LEWIS & BOCKIUS LLP



William O. Trousdell

Reg. No. 38,637

Dated: November 27, 2000

Customer No. 009629

MORGAN, LEWIS & BOCKIUS LLP

1800 M Street, N.W.

Washington, D.C. 20036

(202) 467-7000

A COLOR IMAGE PROCESSING METHOD AND A COLOR IMAGE PROCESSOR

BACKGROUND OF THE INVENTION

The present invention relates to a color image processing
5 method and a color image processor for converting an input color
image signal to a color image recording signal. More
particularly, the present invention relates to a color image
processing method and a color image processor for converting
four or more input color image signals including black to four
10 color image recording signals including black.

With the advancement of computer technologies, network
technologies and color printer technologies in recent years,
the desktop publishing (hereinafter referred to as the DTP)
is getting more and more popular. In the DTP process, printed
15 matters conventionally ordered from a print shop is available
by preparing electronic print manuscript via a computer in an
office or home and outputting the manuscript via a color printer
owned by the office or home in the case of a small number of
copies, and sending the electronic manuscript to the print shop
20 in the case of a large number of copied.

In the case of the DTP, since the target output apparatus
is printing apparatus, it is a common practice to create
electronic print data by using so-called color signals Y, M,
C and K associated with yellow, magenta, cyan and black. A
25 color printer of the electrophotography method or ink-jet

method used for the DTP, it is possible to output images by using the same yellow, magenta, cyan and black as on printed matters.

However, since the image forming method differs between
5 printing and a color printer, the same color materials as in printing may not be available for ink or toner. Even when the same color materials are used for ink or toner, the structure of image or screen image is different thus resulting in a considerable difference in color reproducibility. As a result,
10 the same colors cannot be obtained even if the same signals as the four color signals Y, M, C and K are output on a color printer, the same colors are not obtained.

Thus, a color printer for DTP mounts color conversion apparatus that converts input color signals Y, M, C and K for
15 printing to color signals Y, M, C and K for color printers in order to output colors identical with those for printing on color printers. Such color conversion apparatus generally uses matrix operation, Neural Network, and the direct lookup table (hereinafter referred to as the DLUT).

Here, the matrix operation describes the relationship
20 between input values and output values in the primary or higher determinant and stores the coefficient of the determinant in the ROM (read only memory) or RAM (random access memory) in advance. This approach has advantages that only a small number
25 of parameters are required for color conversion and that the

necessary free space of ROM or RAM is very small. The matrix operation, however, has a disadvantage that it is difficult to obtain a high color consistency accuracy between input and output for input/output characteristics with high non-
5 linearity.

The Neural Network is a description of relationship between input values and output values in the form of the Neural Network. This approach has advantages that only a small number of parameters are required for color conversion and that it
10 is possible to obtain a high color consistency accuracy between input and output for input/output characteristics with high non-linearity. The Neural Network, however, has a disadvantage that it is not suited for real-time processing because of a large amount of operation.

15 The direct lookup table is a table stored in the ROM or RAM in advance that represents the relationship between input values and output values, the input values obtained by a predetermined color conversion coefficient. The direct lookup table has an advantage that color conversion is made
20 at a very high speed, since this approach virtually requires no operation time. The direct lookup table has another advantage that it is possible to obtain a high color consistency accuracy between input and output for input/output characteristics with high non-linearity, since a desired
25 input/output relationship can be specified as a principle.

The DTP assumes output as printed matters so that color signals specified as colors used for electronic manuscript are typically so-called color signals Y, M, C and K associated with yellow, magenta, cyan and black.

5 In recent years, there exists a printing technology using five inks or more called HiFi color aiming at upgrading of picture quality via expansion of color reproducibility. In this technology, six color signals including additional colors, orange and green, are used to represent an electronic manuscript. Whichever color signals are used, black is specified by the editor that prepares the electronic manuscript from respective points of view for text, figures and natural pictures.

15 In particular, text and figures are specified in a single black color for visibility of black text and black thin lines irrespective of the density of the text and the thin lines. Gray representation of figures is either made in the process black composed of yellow, magenta and cyan, or a single black color, depending on the representation intention of the editor.

20 Meanwhile, in natural pictures, photo retouching software or scanner is used to generate the black color by carrying out black addition typically called UCR (under color removal) or GCR (gray component replacement). It is a common practice to skip black addition in an area with lower density
25 and carry out black addition only in an area with higher density,

in order to assure graininess and gradation. Since a larger black addition amount worsens the color reproducibility, the black addition ratio is typically set to as low as around 50 percent in natural pictures.

5 As mentioned earlier, specification of black is different in figures and natural pictures, the same black addition amount is attained both for input and output as intended by the editor in the case of a printed output. Further, areas specified in a single black color is requested to be
10 output in a single black color.

Meanwhile, for color conversion apparatus for DTP, the color conversion method for converting the color signals Y, M, C and K for printing to the color signals Y, M, C and K for color printers is roughly divided into three methods described
15 below.

The first method converts color signals Y, M, C and K for printing to device-independent color signals such as the $L^*a^*b^*$ color signals and then converts the $L^*a^*b^*$ color signals to color signals Y, M, C and K for color printers. The second
20 method splits four color signals Y, M, C and K into three color signals Y, M and C and a color signal K and performs color conversion on three colors Y, M and C so that colorimetric consistency may be obtained between input and output and performs color conversion on the color signal K so that density
25 may be consistent between input and output. The third method

converts four color signals Y, M, C and K for printing to the device-independent color signals and the black addition ratio and converts the device-independent color signals and the black addition ratio to four color signals Y, M, C and K for color printers.

The following methods have been proposed that convert color signals Y, M, C and K for printing to device-independent color signals and then convert the device-independent color signals to color signals Y, M, C and K for color printers. For example, in the Japanese Patent Laid-Open No. 87343/1995, the first Neural Network is used to convert four color signals Y, M, C and K to the $L^*a^*b^*$ color signals as three variable color signals in the device-independent uniform color space, then the second Neural Network is used to convert the $L^*a^*b^*$ color signals to four color signals Y, M, C and K including black.

In the Japanese Patent Laid-Open No. 204973/1996, the first color converter is configured via the Neural Network to convert four color signals Y, M, C and K to the $L^*a^*b^*$ color signals as three variable color signals in the device-independent uniform color space, then the second color conversion operation is configured via the direct lookup table to convert the $L^*a^*b^*$ color signals to four color signals Y, M, C and K including black.

Currently, the color management system (hereinafter referred to as CMS) based on the specifications proposed by

the International Color Consortium (hereinafter referred to as ICC) widely spread as an industry standard basically uses this method to perform color conversion. Examples of representative CMS are ColorSync installed in the MacOS from Apple Corp. or ICM installed in Windows from the Microsoft Corp.

The following is an exemplary method that splits four color signals Y, M, C and K into three color signals Y, M and C and a color signal K and performs color conversion on three colors Y, M and C so that colorimetric consistency may be obtained between input and output and performs color conversion on the color signal K so that density of the color signal K may be consistent between input and output.

For example, in the Japanese Patent Laid-Open No. 65534/1996, the three colors Y, M and C out of the four color signals Y, M, C and K are converted to three color signals Y, M and C that are color-compensated by a higher determinant and the signal K is converted to the signal K that is gradation-compensated by the one-dimensional lookup table (hereinafter referred to as LUT).

In the Japanese Patent Laid-Open No. 116458/1996, three colors Y, M and C out of the four color signals Y, M, C and K are converted to three color signals Y, M and C that are color-compensated by the three-dimensional direct lookup table and the signal K is converted to the signal K that is gradation-compensated by the one-dimensional lookup table.

The following is an exemplary method that converts four color signals Y, M, C and K for printing to the device-independent color signals and the black addition ratio and converts the device-independent color signals and the black addition ratio to four color signals Y, M, C and K for color printers.

For example, in the Japanese Patent Laid-Open No. 186894/1997, four color signals Y, M, C and K are converted to the $L^*a^*b^*$ color signals as device-independent three variable color signals and the black addition ratio via first conversion means and converts the $L^*a^*b^*$ color signals and the black addition ratio to four color signals Y, M, C and K.

The method that converts color signals Y, M, C and K for printing to $L^*a^*b^*$ color signals as device-independent color signals and converts the $L^*a^*b^*$ color signals to color signals Y, M, C and K for color printers, proposed in the Japanese Patent Laid-Open No. 87343/1995 and Japanese Patent Laid-Open No. 204973/1996, is effective in that colorimetric consistency may be obtained between input and output. However, since the output black amount is determined irrespective of the input black amount, this method has a problem that the input black amount is inconsistent between input and output.

Moreover, since color characteristics of black color for printing or color printer differ with difference of color materials and image structure, there arises an essential

problem that output of black text or black thin lines with a black addition ratio of 100 percent results in colorimetrically consistent gray of the four color signals Y, M, C and K, not in reproduction in a single black color. When three colors
5 Y, M and C are added to black text or black thin lines to be reproduced in a single black color, the text or the thin lines are colored in the presence of wear of color or poor transfer thus worsening the picture quality.

When the black addition ratio is set to 100 percent
10 focusing on reproduction of black text or black thin lines, the black addition amount is too large in natural pictures thus worsening graininess, gradation and color reproducibility.

The method that splits four color signals Y, M, C and K into three color signals Y, M and C and a color signal K and
15 performs color conversion on three colors Y, M and C so that colorimetric consistency may be obtained between input and output and performs color conversion on the color signal K so that the density of the color signal K may be consistent between input and output, proposed in the Japanese Patent Laid-Open
20 No. 65534/1996 and Japanese Patent Laid-Open No. 116456/1996, can obtain the consistency of the black addition amount between input and output thus reproducing black text and black thin lines specified in a single black color in a manuscript.

The method is effective in that colorimetric consistency
25 of three colors Y, M and C is obtained. However, color

reproducibility of color printers has a poor non-linearity and a very poor non-linearity in case black color is added. Thus, it is difficult to obtain colorimetric consistency of colors represented in four color signals Y, M, C and K even when consistency is obtained for colorimetric values of three colors Y, M and C and the density of the color K, respectively. In particular, when matrix operation is used in color converter as mentioned in the Japanese Patent Laid-Open No. 85535/1996, it is difficult to obtain a high color consistency between printing and color printers even when a higher determinant is used.

The method that converts four color signals Y, M, C and K for printing to device-independent color signals and the black addition ratio and converts the device-independent color signals and the black addition ratio to four color signals Y, M, C and K for color printers, proposed in the Japanese Patent Laid-Open No. 186894/1997, is effective in that colorimetric consistency of colors is obtained between input and output and consistency of black addition ratio is obtained between input and output.

However, since color characteristics of four color signals Y, M, C and K including black color for printing or color printer differ with difference of color materials and image structure, black addition amount is not perfectly consistent between input and output, even when the black

addition ratio is made consistent. Further, same as the method proposed in the Japanese Patent Laid-Open No. 87343/1995 or the Japanese Patent Laid-Open No. 204973/1996, there is a problem that black text and black thin lines specified in a single black color in a manuscript is represented in the process black composed of four colors Y, M, C and K that are colorimetrically consistent.

SUMMARY OF THE INVENTION

10 The invention is intended to eliminate the foregoing disadvantages of the related art. The invention aims at providing a color image processing method and a color image processor that can match the black addition amount for printing as an input with the black addition amount for color printers as an output, reproduce in a single black color text and figures 15 are specified in a single black color in a manuscript, and match colorimetric colors between input and output.

The invention is a color image processing method and a color image processor to attain the foregoing object. A color 20 image processing method according to the invention is intended to convert first color signals containing four or more variables including black to second color signals containing four variables including black and comprises a step for obtaining device-independent color signals on color system 25 color coordinates, a step for determining a black color signal

in the second color signals having the identical or virtually identical density as the black color signal in the first color signals, and a step for determining the remaining three variable color signals in the second color signals from the
5 black color signal and the device-independent color signals in the second color signals so that colorimetric consistency of the three variable color signals may be obtained.

Color image processing apparatus according to the invention is intended to convert first color signals containing
10 four or more variables including black to second color signals containing four variables including black and comprises means for obtaining device-independent color signals on color system color coordinates, means for determining the black color signal in the second color signals having the identical or virtually
15 identical density to that of the black color signal in the first color signals, and means for determining the remaining three variable color signals in the second color signals from the black color signal and the device-independent color signals in the second color signals so that colorimetric consistency
20 of the three variable color signals may be obtained.

In the invention, device-independent color signals on color system color coordinates are obtained from the first color signals containing four or more variable color signals including black and the black color signal in the second color
25 signals having the identical or virtually identical density

to that of the black color signal in the first color signals is determined. From the determined black color signal in the second color signals and the previously obtained device-independent color signals, the remaining three variable color signals in the second color signals are determined so that colorimetric consistency of the three variable color signals may be obtained. As a result, density of the black color signal can be made consistent between the first color signals and the second color signals, and colorimetric consistency of the three variables other than the black color may be obtained.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of a color DTP system that uses a color image processor according to the invention.

Fig. 2 is a schematic block diagram of image output apparatus according to the invention.

Fig. 3 shows details of color conversion processing by color conversion means.

Fig. 4 shows an example of one-dimensional lookup table.

Fig. 5 shows comparison between the invention and the related art.

Fig. 6 is a block diagram that shows the main sections of the second embodiment.

Fig. 7 shows the steps for determining color conversion parameters.

Fig. 8 is a block diagram that shows the main sections of the third embodiment.

Fig. 9 shows the steps for determining color conversion parameters.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of a color image processing method and a color image processor according to the invention will be explained below with reference to figures. Fig. 1 is a block diagram of the color DTP system that uses color image processor according to the invention. The entire color DTP system is composed of manuscript editing apparatus 100, image processor 200 and image output apparatus 300.

The manuscript editing apparatus 100 is apparatus that prepares electronic printing manuscripts and outputs electronic manuscript data including a page description language and raster image data onto the image processor 200. In particular, the manuscript editing apparatus 100 either edits manuscripts by using a variety of applications on a personal computer (PC), or edits manuscripts on a dedicated computer.

When the manuscript editing apparatus 100 edits manuscripts on a PC, it edits electronic manuscripts by using DTP software such as the PagemakerPro from Adobe Systems and QuarkXPress from Quark Company on a Macintosh or IPM-PC.

Prepared electronic manuscripts are converted for example by the PostScript printer driver from the Adobe Systems to PostScript as a page description language then output to the image processor 200 via a network such as the Ethernet.

- 5 While PostScript is used as a page description language to be sent from a PC for DTP to the image processor 200, any other page description language can be used.

- 10 When the manuscript editing apparatus 100 uses a dedicated computer, it edits electronic manuscripts via a dedicated workstation and application called the Color Electronic Prepress System (hereinafter referred to as CEPS). Prepared electronic manuscripts are output to the image processor 200 via a network such as the Ethernet, in the raster information format, for example, in the TIFF/IT format as
15 standard specifications for raster image data or Scitex format in widespread use as printing electronic data.

While the TIFF/IT is used as raster information to be sent from the CEPS to the image processor 200, any image format as raster format image data can be used.

- 20 Color signals for an electronic manuscript assumes output in printing. Thus, the so-called color signals Y, M, C and K associated with yellow, magenta, cyan and black are used to specify colors for an electronic manuscript. Recently, a printing technology is available that uses inks of four or
25 more colors called HiFi color, aiming at upgrading of picture

quality via expansion of color reproducibility. In this technology, eight color signals including additional colors, orange and green, are used to represent an electronic manuscript. While color signals for electronic manuscripts are color signals Y, M, C and K, color signals containing four or more colors, in particular black, are applicable.

The entire image processor 200 is composed of editing apparatus communication means 210, format conversion means 220, rasterizing means 230, color conversion means 240 and output apparatus communication means 250. Electronic manuscripts in code information or raster information input from the manuscript editing means 100 are converted to a format that can be output to image output apparatus 300 via the image processor 200.

Electronic manuscripts specified in four color signals Y, M, C and K sent from the manuscript editing apparatus 100 are transferred to the image processor 200 via a network such as the Ethernet by the editing apparatus communication means 210. A page description language such as PostScript is converted by the rasterizing means 230 to raster-format image data that can be output to the image output apparatus 300.

Raster-format image data such as TIFF/IT undergoes resolution conversion and format conversion and converted to raster-format image data that can be output to the image output apparatus 300, via the format conversion means 220.

Four color signals Y, M, C and K transferred from the rasterizing means 230 and the format conversion means 220 are converted by the color conversion means 240 to four image recording signals Y, M, C and K associated with yellow, magenta, cyan and black as image recording signals in the color space for the image output apparatus 300.

Image recording signals color-converted by the color conversion means 240 are transferred to the output apparatus communication means 250. The output apparatus communication means 250 stores image recording signals processed by the image processor 200 and transfers the image recording signals to the image output apparatus 300 as required to offset the difference of processing speed between the image processor 200 and the image output apparatus 300. On the image output apparatus 300, target image is formed on paper according to four raster-format image recording signals Y, M, C and K.

In this embodiment, the ULTRA workstation from the SUN Microsystems Corp. is used as a platform for the image processor 200. The Ethernet controller installer in the workstation is used as the editing apparatus communication means 210. Further, the format conversion means 220 is configured via software using C language on the Solaris that is the UNIX-OS from the SUN Microsystems Corp.

As the rasterizing means 230, the rasterizing software CPSI from Adobe Systems is used. The color conversion means

240 is configured via software using C language on the Solaris. The output apparatus communication means 250 is configured by large-capacity memory and dedicated hardware for communications with the image output apparatus 300 on the PCI bus of the ULTRA workstation, with data input/output controlled via software on Solaris.

In this embodiment, the image processor 200 is configured by installing dedicated hardware and software in a general-purpose computer. Configuration of the image processor 200 is not limited to this configuration but may be configured by a combination of dedicated hardware and software. The portion realized by software may be realized by hardware and the portion realized by hardware may be realized by software.

It is possible to configure the system so as to reduce memory capacity necessary for storage of image data thus reducing hardware costs, by compressing and storing image data in the output apparatus communication means 250 and decompressing and transferring the data to the image output apparatus 300. In this case, it is possible to use a low-cost hard disk instead of an expensive memory thereby compressing image data.

Fig. 2 is a schematic block diagram of the image output apparatus according to this embodiment. In Fig. 2, the sign 50 is an intermediate transfer belt and supported by rollers

5-1, 5-2, 5-3, 5-4 and a heating roller 2 to transfer picture images in the direction of the arrow. A heating roller 3 is arranged face to face with the heating roller 2.

Four photo conductors 1-1, 1-2, 1-3 and 1-4 are uniformly
5 charged by chargers for preparing electrostatic latent images
15, 16, 17 and 18. Image recording signals Y, M, C and K
transferred from the image processor undergoes horizontal scan
to form electrostatic latent images on the four photo
conductors 1-1, 1-2, 1-3 and 1-4 by laser scanner apparatus
10 390.

Next, on the electrostatic four photo conductors 1-1,
1-2, 1-3 and 1-4 where electrostatic latent images are formed,
toner images in black, yellow, magenta and cyan are
respectively formed by a black processor 11, a yellow processor
15 12, a magenta processor 13 and a cyan processor 14. These toner
images are sequentially transferred to the intermediate
transfer belt by transfer units 50-1, 50-2, 50-3 and 50-4 to
form toner images in a plurality of colors on the intermediate
transfer belt.

20 After that, recording paper fed by a paper feeder 7 from
a paper tray 8 is heated while being wound around the heating
roller 3 via pin rollers 9-1 and 9-2 attached to a winding
mechanism 8, then pressurized and heated in close contact with
the intermediate transfer belt 50 by the heating roll 2 and
25 the heating roll 3. This causes the toner to be transferred

on the recording paper. The intermediate transfer belt 50 and the recording paper pressurized and heated by the heating roll 2 and the heating roll 3 move in close contact and cooled by cooling apparatus 4.

5 Thus, the toner transferred on the recording paper is solidified and generates a strong adhesive strength and fixed on the recording paper. Then, on the small-curvature toll 5-1, the recording paper is detached together with the toner from the intermediate transfer belt 50 due to the stiffness of the
10 recording paper, to form a color image.

As photo conductors 1-1, 1-2, 1-3 and 1-4, various types of organic photo conductors can be used as well as various types of inorganic photo conductors such as Se, a-Si, a-SiC and CdS. The toner is composed of a thermoplastic binder containing
15 pigments such as yellow, magenta and cyan and can use known materials. In this embodiment, polyester toner of a weight molecular weight of 54000, a softening point of 1130 °C and an average grain diameter of 7 micrometers is used.

The aforementioned exposure conditions and processing
20 conditions is set so that the toner amount of each color on recording media may fall within the range of about 0.4 mg/cm² to 0.7 mg/cm² depending on the content of pigments. In this embodiment, 0.65 mg/cm² is specified for each color. The recording media is plain paper or coated paper on the market.
25 In this embodiment, J-coat paper from Fuji Xerox Co., Ltd. is

used.

The intermediate transfer belt 50 is composed of two layers, the base layer and the surface layer. The base layer is a polyimide film $70\mu\text{m}$ in thickness with black carbon added.

- 5 The volume resistivity is adjusted to $10^{10}\Omega\text{cm}$ with additive amount of carbon black changed. As the base layer, for example, a high heat-resistant sheet 10 to $300\mu\text{m}$ in thickness can be used. A polymer sheet of polyester, polyethylene terephthalate, polyether sulfone, polyether ketone, 10 polysulfone, polyimide, polyimide amide, or polyamide.

- The volume resistivity of the surface layer is adjusted to $10^{14}\Omega\text{cm}$ in order to transfer toner images from a photo conductor to an intermediate transfer belt without electrostatic disturbance of images. In order to sandwich a 15 toner image and improve adhesion of the intermediate transfer belt and paper in simultaneous transfer and fixing from the intermediate transfer belt to the paper, a silicon copolymer of 40 degrees in rubber hardness and $50\mu\text{m}$ in thickness.

- The silicon copolymer shows tackiness to toner at room 20 temperatures. To transfer toner to recording media efficiently, the silicon copolymer has characteristic of easily releasing melted and fluidized toner. Thus the silicon copolymer is an optimum material as a surface layer. It is possible to use a resin layer 1 to $100\mu\text{m}$ in thickness with 25 high mold releasing capability as a surface layer. For example,

it is possible to use tetrafluoroethylene-perfluoroalkyl vinyl ether copolymer and polytetrafluoroethylene.

As a heating roller, it is possible to use a metallic roller or a metallic roller equipped with a heat-resistant elastic layer. Inside the heating roller is arranged a heat source, whose set temperature is determined by the thermal melting property of toner and a thermoplastic resin layer on the recording paper. Here, the softening point of toner should be higher than the softening point of a resin layer, temperature setting is made so that the set temperature of the heating roller 2 may exceed the set temperature of the heating roller 3. In this embodiment, the heating roller 2 is set to 150 °C and the heating roller 120 °C, respectively.

While the pressure of the heating roll 2 and heating roll 3 in transfer and fixing is set to 5 kgf/cm², the pressure value is not limited to this value but may fall within the range of 1 kgf/cm², to 10 kgf/cm². The diameter of the heating roller 3 is 5 mm and the revolution speed of the heating rollers is set so that the carrying speed of the intermediate transfer body may reach 240 mm/sec.

In this embodiment, the temperature on the surface of the recording media that comes in contact with the intermediate transfer belt, assumed when the media is released from the intermediate transfer belt is set to 70 °C, by adjusting the wind amount of the cooling apparatus 4.

While a color printer of the tandem engine electronic photography system is applied as image output apparatus 300 in this embodiment, the image output apparatus is not limited to this but a system may be used in which a heat-resistant belt photo conductor is used instead of the single engine system or intermediate transfer belt, to directly transfer and fix a plurality of toner images formed on the belt photo conductor.

The image output apparatus 30 is not limited to a color printer of the electronic photography system but any output apparatus may be used that records images by using four-variable color signals, in particular color signals Y, M, C and K. For example, ant color image output apparatus such as printing, ink-jet system, thermal transfer system and silver halide system may be used.

Next, the color conversion means 240 that is a main section of this embodiment will be described. Fig. 3 shows details of the color conversion processing via the color conversion means 240. Out of the four color signals Y, M, C and K as the first color signals transferred from the rasterizing means 230 and the format conversion means 220, four color signals Y, M, C and K are input to the device-independent color space converter 241, a color signal K to the gradation compensator 242, and three color signals Y, M and C to the YMC judgment section 244.

Four color signals Y, M, C and K input to the

device-independent color space converter 241 are converted to the $L^*a^*b^*$ color space as a device-independent color space and input to the YMC decision section 243. The color signal K input to the gradation compensator 242 is converted to the image recording signal for the image output apparatus 300, that is, a color signal K' having the equivalent lightness out of the second color signals Y', M', C' and K', then transferred to the YMC decision section 243 and a YMCK output section 246.

The YMC judgment section 244 judges the case where input three color signals Y, M and C are simultaneously zero and sends the judgment flag to a YMC correction section 245. The YMC decision section 243 determines color signals Y', M' or C' for the image output apparatus 300 that is identical with the $L^*a^*b^*$ color signal input with its black addition amount being under conditions of the color signal K', from the color signal $L^*a^*b^*$ input from the device-independent color space converter 241 and the signal K' input from the gradation compensator 242.

The YMC correction section 245, on receiving the judgment flag from the YMC judgment section, sets all the color signals Y', M' and C' input from the YMC decision section 243 to zero and transfers the signals to the YMCK output section 246. The YMCK output section 246 transfers the color signals Y', M' and C' input from the YMC correction section 245 and the color signal K' input from the gradation compensator 242 to the output apparatus communication means 300.

The device-independent color space converter 241 can use a color conversion circuit of the matrix operation type, a color conversion circuit of the direct lookup table, and a color conversion circuit of the Neural Network type, each of which is in widespread use as a color conversion circuit.

The color conversion coefficient of the device-independent color space converter 241 is determined in the following way. First, a patch is output for printed material corresponding to an arbitrary combination of color signals Y, M, C and K for printing input from the manuscript editing apparatus 100. The colorimetric values ($L^*a^*b^*$) of the patch are measured via a colorimeter on the market to obtain the colorimetric values for printing ($L^*a^*b^*$) corresponding to color signals Y, M, C and K to be input and model the conversion characteristics of the colorimetric values ($L^*a^*b^*$) for the input data (Y, M, C, K).

While a higher polynomial or Neural Network is used for such a model, in this embodiment, the Neural Network is instructed to study a data set comprising a combination of YMCK data and $L^*a^*b^*$ data, and the color characteristics of printing to be input are modeled. The device-independent color space converter 241 uses the obtained Neural Network in the color converter without modification.

In this embodiment, the Neural Network as defined in *K. Murai, Furekishiburu UCR niyoru kouseido irohenkan ~ Neural*

Network niyoru kouseido purinntamoderu~, Japan Hard Copy '94
ronnbunshuu, pp.181-184 is used as a Neural Network and study
is performed via the back propagation method.

While the representative color space used as standard
5 colors in the printing industry is SWOP in the U.S.A. and
JapanColor in Japan, the color conversion coefficient of the
JapanColor is obtained in this embodiment. As a data set used
for obtaining the color conversion coefficient, JapanColor 928
patch colorimetric data standardized in the international
10 standard ISO12642 is used. Other color space and data sets
for printing may be used to obtain the color conversion
coefficient.

The device-independent color space converter 241 can
typically use the color space that converts input color signals
15 to the $L^*a^*b^*$ color space. While the following example
pertains to a case where input color signals are converted to
the $L^*a^*b^*$ color space, conversion to another color space, such
as the XYZ color space or $L^*a^*b^*$ color space is allowed. Note
that conversion to a perceptual uniform color space is
20 desirable.

Further, the device-independent color space converter
241 may be adapted to input color signals containing five or
more colors including black, as well as four color signals Y,
M, C and K. Color signals containing five or more colors
25 include, for example, HiFiColor containing six colors, that

is, four colors Y, M, C and K plus green and orange. Color signals containing five or more colors can be converted to the device-independent color space via similar means and method. In case color signals containing for example six colors are
5 input, the 6-input 3-output Neural Network can be applied to the device-independent color space converter 241.

In the gradation compensator 242, the one-dimensional lookup table is used to convert an input signal K for printing to a color signal K' for the image output apparatus 300 that
10 has an equivalent lightness. Fig. 4 shows an example of one-dimensional lookup table that converts an input black addition amount K for printing to an input black addition amount K' for the image output apparatus 300.

In Fig. 4, horizontal axis and vertical axis show the
15 8-bit quantified values of the screen coverage ratio of black addition amount K and K', respectively. In creating a lookup table, lightness L^* assumed when the screen coverage ratio is changed from 0 to 255 is measured in advance, and the value of the output black addition amount K' that has the lightness
20 equivalent to the lightness L^* of the input black addition amount K is obtained, then set as a lookup table value.

In this embodiment, in order to precisely compensate for the gradation of the input/output black addition amount, one-dimensional lookup table is used as the gradation
25 compensator 242. However, any mechanism that can describe the

one-dimensional input/output relationship, such as a function formula, is applicable, and the number of quantifying divisions of the lookup table is not limited to 8 bits.

While the conversion characteristics of the gradation compensator 242 are specified so that consistency of lightness of black addition amount may be obtained between input and output, setting can be made so that consistency of density of black addition amount may be obtained between input and output. It is desirable that the exact consistency of lightness or density may be obtained between input and output. However, conversion characteristics can be specified so that equivalent lightness or density may be obtained, not the exactly identical lightness or density.

The YMC decision section 243 obtains the relationship between image recording signals Y' , M' , C' and K' and the colorimetric values $L^*a^*b^*$ in the device-dependent color space in advance. This relationship is hereinafter referred to as the color conversion model. The YMC decision section 243 then numerically solves the color conversion model from the $L^*a^*b^*$ color signals obtained from the device-independent color space converter 241 and the color signal K' obtained from the gradation compensator 242 to determine the remaining three color signals Y' , M' and C' for the image output apparatus 300 that are colorimetrically identical to the input $L^*a^*b^*$, with black addition amount for the image output apparatus 300 being

K'.

How to prepare the color conversion model for the image output apparatus 300 is described below. First, a color patch is output corresponding to an arbitrary combination of image recording signals color signals Y, M, C and K for the image output apparatus 300 is printed out on the image output apparatus 300 and the colorimetric values $L^*a^*b^*$ of the patch are measured via a colorimeter.

In this embodiment, a combination of $6 \times 6 \times 6 \times 6 = 1296$ patches with the screen coverage ratio of each color being incremented by 20% is printed out as a combination of image recording signals Y', M', C' and K', on the image output apparatus 300. Then, the colorimetric values $L^*a^*b^*$ in a field of 2 degrees are measured under the measurement conditions of D50, by using the colorimeter X-Rite 938 from the X-Rite Company. While an arbitrary number of color patches may be used for measurement, it is desirable to use as many patches as possible for a higher-accuracy color conversion model.

While the uniform color space $L^*a^*b^*$ color system is used as a color system for measurement in this embodiment, another color system such as the XYZ color system may be used. Note that a uniform color space is preferable in order to evaluate the color difference in solving the color conversion model.

Next, the Neural Network is instructed to study a data set of plural signals Y', M', C' and K' and $L^*a^*b^*$ obtained

as instructor data. The relationship between the signals Y' , M' , C' and K' and $L^*a^*b^*$ is represented by the following function.

$$(L^*, a^*, b^*) = F(Y', M', C', K') \quad (1)$$

- 5 where, formula (1) is dissolved into color components:

$$L^* = FL(Y', M', C', K') \quad (2)$$

$$a^* = Fa(Y', M', C', K') \quad (3)$$

$$b^* = Fb(Y', M', C', K') \quad (4)$$

In this embodiment, the Neural Network as defined in K .

- 10 *Murai, Furekishiburu UCR niyoru kouseido irohenkan ~ Neural Network niyoru kouseido purinntamoderu~, Japan Hard Copy '94 ronbunshuu, pp.181-184* is used as a Neural Network and study is performed via the back propagation method. While the Neural Network is used as a color conversion model in this embodiment,
- 15 it is possible to apply another polynomial model or color conversion model of conversion table system.

- Next, numerical solution of the color conversion model will be described. The inverse function of the ordinary function F is not obtained. However, in case $L^*a^*b^*$ is given
- 20 and one variable out of Y' , M' , C' and K' is properly determined, the remaining three variables can be obtained from the formula (1). For example, in case K' is given, Y' , M' and C' is determined. Assuming the colors to be reproduced as $L^*a^*b^*$ and black addition amount as K' , color difference ΔE between
- 25 colors to be reproduced and the image recording signals Y' ,

M' and C' and black addition amount K' is defined as a function of image recording signals Y', M' and C' in the following formula.

$$\Delta E (Y', M', C') = ((L^* - FL(Y', M', C', K'))^2 + (a^* - Fa(Y', M', C', K'))^2 + (b^* - Fb(Y', M', C', K'))^2)^{1/2} \quad (5)$$

Solving the non-linear equation (1) is the same as obtaining the values of Y', M' and C' assumed when the color difference ΔE equals zero. Thus, the procedure for solving the equation (1) may be considered as a non-linear optimization problem of Y', M' and C' that minimizes the objective function ΔE by making the color difference ΔE the objective function. Therefore, it is possible to solve the equation (1) by using the non-linear optimization approach such as the simplex method.

For the simplex method, corresponding algorithm is introduced, for example, in H.Konno, *Hisenkei keikakuho*, Nikkagirensheppansha, pp.284-286. The simplex method is an approach suited for optimization of a multi-variable function and allows the optimized value to be obtained at a high speed.

In this embodiment, the simplex method that can optimize a multi-variable function at a high speed as a non-linear optimization approach is applied. Any non-linear optimization approach may be used and other non-linear optimization approaches such as the dichotomy and the golden

section exploration method may be applied. Numerical solution of a non-linear equation such as the Newton method may be applied to solve the color conversion model.

In this way, it is possible to determine the remaining
5 three color signals Y' , M' and C' for the image output apparatus 300 that are colorimetrically identical to the input $L^*a^*b^*$, with black addition amount for the image output apparatus 300 being K' , from the $L^*a^*b^*$ color signals obtained from the device-independent color space converter 241 and the color
10 signal K' obtained from the gradation compensator 242.

The YMC judgment section 244 judges whether or not the three input color signals Y , M and C are simultaneously zero, and sends the judgment flag to a YMC correction section 245. The YMC correction section 248, on receiving the judgment flag
15 from the YMC judgment section 244, sets all the image recording signals Y' , M' and C' input from the YMC decision section 243 to zero. As a result, it is possible to reproduce black text and black thin lines represented in a single black color in a manuscript, thereby considerably upgrading the
20 reproducibility of black text and black thin lines.

Meanwhile, for the portion where a single black color is specified for input and output, a small color difference will result by correcting the color signals Y' , M' and C' even when the consistency of lightness is obtained, due to
25 difference in the color material or image structure between

printing and the image output apparatus 300. This color difference is, however, negligible visually.

In the invention, for the portion where a single black color is not specified in an electronic manuscript, 5 colorimetric consistency is assured in principle. Thus, it is possible to obtain visually exact consistency between the printing color specified in the input electronic manuscript and the color printed on the image output apparatus 300.

This embodiment is configured so that the YMC correction 10 section 244, on receiving the judgment flag from the YMC judgment section 244, sets all the image recording signals Y', M' and C' input from the YMC decision section 243 to zero. Correction of Y', M' and C' may be skipped when more accuracy in color consistency between input and output is desired.

15 In case the color characteristics of the input color signals Y, M, C and K for printing are close to those of the color signals Y, M, C and K for color printers, reproduction of black text or black thin lines in a single black color may be acceptable visually even when correction of Y', M' and C' 20 by the YMC correction section 245 is skipped. In such a case also, it is possible to skip correction of Y', M' and C' by the YMC correction section 245. Note that it is preferable to perform correction of Y', M' and C' by the YMC correction section 245 as in this embodiment, in order to assure 25 reproduction of black text and black thin lines in a single

black color.

Finally, color conversion processing by the color conversion means completes when the YMCK output section 246 transfers image recording signals Y', M', C' and K' to be input
5 to the image output apparatus 300 via the output apparatus communication means 250.

In order to check the validity of the invention, Fig. 5 shows the evaluation results of the color conversion accuracy and reproduction of black text or black thin lines in a single
10 black color on five configurations: a configuration in which the color conversion means is adapted according to the embodiment of the invention; a configuration in which color signals Y, M, C and K for printing are converted to device-independent color signals and then to color signals Y',
15 M', C' and K' for the image output apparatus 300, represented by the Japanese Patent Laid-Open No. 87343/1995; a configuration in which four color signals Y, M, C and K are split into three color signals Y, M and C and a color signal K and color conversion is performed on three colors Y, M and
20 C by using a higher determinant and color conversion is performed on the color signal K by using one-dimensional lookup table, represented by the Japanese Patent Laid-Open No. 65534/1996; a configuration in which four color signals Y, M, C and K are split into three color signals Y, M and C and a
25 color signal K and color conversion is performed on three colors

Y, M and C by using a third-dimensional lookup table and color conversion is performed on the color signal K by using one-dimensional lookup table, represented by the Japanese Patent Laid-Open No. 118456/1996; and a configuration in which

5 color signals Y, M, C and K for printing are converted to device-independent color signals and the black addition ratio and the device-independent color signals and the black addition ratio are converted to color signals Y', M', C' and K' for image output apparatus 300, represented by the Japanese Patent

10 Laid-Open No. 186894/1997.

To the configuration of the color conversion means 240 other than the invention, the embodiment of the related art as shown previously is shown as it is. As a color conversion accuracy, the average value and the maximum value of the color

15 difference in colorimetric value between the color patch data on 928 data pieces for printing that conforms to ISO12842 and the printout on the image output apparatus 300. For reproduction in a single black color, the mark \bigcirc is given when data specified in a single black color in an electronic

20 manuscript can be reproduced perfectly in a single black color on the image output apparatus, and the mark \times otherwise.

As understood from Fig. 5, according to a method in which color signals Y, M, C and K for printing are converted to device-independent color signals and then to color signals Y',

25 M', C' and K' for the image output apparatus 300, represented

by the Japanese Patent Laid-Open No. 87343/1995, and a method in which color signals Y, M, C and K for printing are converted to device-independent color signals and the black addition ratio and the device-independent color signals and the black addition ratio are converted to color signals Y', M', C' and K' for image output apparatus 300, represented by the Japanese Patent Laid-Open No. 186894/1997, reproduction in a single black color is impossible although the color conversion accuracy is high.

- 10 It is understood that, according to a method in which four color signals Y, M, C and K are split into three color signals Y, M and C and a color signal K and color conversion is separately performed on three colors Y, M and C, and on the color signal K, represented by the Japanese Patent Laid-Open
- 15 No. 65534/1996 and the Japanese Patent Laid-Open No. 116456/1996, the color conversion accuracy is very low although reproduction in a single black color is possible.

- The invention, while reproduction in a single black color is possible, a high color conversion accuracy equivalent to
- 20 that in the Japanese Patent Laid-Open No. 87343/1995 and the Japanese Patent Laid-Open No. 188894/1997 is realized, and both the high color reproducibility and favorable reproduction of black text and black thin lines are realized.

- As mentioned earlier, device-independent color signals
- 25 $L^*a^*b^*$ on the color system color coordinates are obtained from

four color signals Y, M, C and K specified by the manuscript editing apparatus. A black color signal K' for the image output apparatus 300 is determined that has the lightness equivalent to the lightness of the input black color signal K. From the
5 determined black color signal K' and the device-independent color signals $L^*a^*b^*$, the remaining three variable color signals Y, M' and C' are determined by solving the color conversion model for the image output apparatus 300 by using the numerical solution, so that colorimetric consistency
10 between the remaining three variable color signals Y, M' and C' and the device-independent color signals $L^*a^*b^*$ may be obtained. When color signals Y, M and C other than the input signal K are all zero, the remaining three variable color signals Y', M' and C' are corrected to be zero. In this way,
15 both the high color consistency between input and output and favorable reproduction in a single black color of black text and black thin lines specified in a single black color in an electronic manuscript, with a consistent lightness, are realized.

20 Next, the second embodiment of the invention will be described. While the second embodiment of the invention is similar to the configuration shown in Fig. 1, like the first embodiment, the configuration of the color conversion means 240 is different. The remaining configuration is the same as
25 that of the first embodiment. Fig. 6 is a block diagram of

the main sections of the second embodiment. In this embodiment, the color conversion means 240 is configured by a 4-input 4-output four-dimensional DLUT color converter 247.

5 The four-dimensional DLUT color converter 247 is configured by a four-dimensional direct lookup table that uses the value obtained by dividing each axis of input color signals Y, M, C and K by 16 as an input address and performs interpolation operation via cubic interpolation to calculate image recording signals Y', M', C' and K' for the image output apparatus 300.

10 While the cube interpolation is applied as an interpolation system for the direct lookup table in this embodiment, other known systems such as the prism interpolation and tetrahedral interpolation may be applied. Number of divisions of each input axis may be other than 16.

15 While the color conversion means 240 is configured by a four-dimensional direct lookup table in this embodiment, this is not limiting but any known color conversion system such as the Neural Network may be applied as long as 4-input 4-output color conversion is realized.

20 In this embodiment, the color conversion means does not limit the input color signals to four color signals Y, M, C and K but color signals containing five or more colors including black may be input. Four color signals used for printing include, for example, HiFiColor containing six colors, that
25 is, four colors Y, M, C and K plus green and orange.

Color signals containing five or more colors can be converted to the image recording signals containing four colors via similar means and method. For example, in case six color signals are input, a 6-input 4-output six-dimensional direct
5 lookup table may be applied to the color conversion means.

Fig. 7 shows the steps for determining color conversion parameters for the four-dimensional DLUT color converter in this embodiment. In step 1, a patch is output for printed material corresponding to an arbitrary combination of color
10 signals Y, M, C and K for printing input from the manuscript editing apparatus 100. The corresponding colorimetric values $L^*a^*b^*$ are measured via a colorimeter on the market.

Then, the colorimetric values $L^*a^*b^*$ in a field of 2 degrees are measured under the measurement conditions of D50,
15 by using the colorimeter X-Rite 938 from the X-Rite Company. While an arbitrary number of color patches may be used for measurement, it is desirable to use as many patches as possible for a higher-accuracy color conversion model.

While the uniform color space $L^*a^*b^*$ color system is used
20 as a color system for measurement in this embodiment, another color system such as the XYZ color system may be used. As a color space and a data set for printing, JapanColor 928 patch colorimetric data standardized in the international standard ISO12642 is used. Other color space and data sets for printing
25 may be used.

In step 2, the Neural Network is instructed to study a data set of plural signals Y, M, C and K and $L^*a^*b^*$ obtained in step 1 as instructor data. In this embodiment, this Neural Network is called Neural Network1. While a higher polynomial, conversion table system or Neural Network is generally used for such a color conversion model, the Neural Network is instructed to study a data set comprising a combination of YMCK data and $L^*a^*b^*$ data to model the input color characteristics for printing in this embodiment.

10 In this embodiment, a Neural Network similar to that in the first embodiment is used and study is performed via the back propagation method. Input color signals are not limited to four color signals Y, M, C and K but color signals containing five or more colors including black may be input.

15 Next, in step 3, a color patch corresponding to an arbitrary combination of image recording signals Y' , M' , C' and K' for the image output apparatus 300 is printed out on the image output apparatus 300 and the corresponding colorimetric values $L^*a^*b^*$ are measured via a colorimeter.

20 In this embodiment, a combination of $6 \times 6 \times 6 \times 6 = 1296$ patches with the screen coverage ratio of each color being incremented by 20% is printed out as a combination of image recording signals Y' , M' , C' and K' , on the image output apparatus 300. Then, the colorimetric values $L^*a^*b^*$ in a field of 2 degrees
25 are measured under the measurement conditions of D50, by using

the colorimeter X-Rite 938 from the X-Rite Company.

While the uniform color space $L^*a^*b^*$ color system is used as a color system for measurement in this embodiment, another color system such as the XYZ color system may be used. Note
5 that a uniform color space is preferable in order to evaluate the color difference in solving the color conversion model.

In step 4, the Neural Network is instructed to study a data set of plural signals Y' , M' , C' and K' and $L^*a^*b^*$ obtained as instructor data. In this embodiment, this Neural
10 Network is called Neural Network 2. In this embodiment, a Neural Network similar to that in the first embodiment is used and study is performed via the back propagation method.

In step 5, colorimetric values $L^*a^*b^*$ for the input address values Y , M , C and K of the four-dimensional DLUT color
15 converter 247 are determined by using the Neural Network obtained in step 2.

Next, in step 6, black addition amount K' for the image output apparatus 300 that has an equivalent lightness to that of the input address value K of the four-dimensional DLUT color
20 converter 247 is determined by using the one-dimensional lookup table. In this embodiment, same as the first embodiment, the number of quantifying divisions of the one-dimensional lookup table is 8 bits. In creating a lookup table, lightness L^* assumed when the screen coverage ratio is changed from 0 to
25 255 is measured in advance, and the value of the output black

addition amount K' that has the lightness equivalent to the lightness L^* of the input black addition amount K is obtained, then set as a lookup table value.

In this embodiment, in order to precisely compensate for the gradation of the input/output black addition amount, one-dimensional lookup table is used in step 6. However, any mechanism that can describe the one-dimensional input/output relationship, such as a function formula, is applicable, and the number of quantifying divisions of the lookup table is not limited to 8 bits.

Setting can be made so that consistency of density of black addition amount may be obtained between input and output. Conversion characteristics can be specified so that equivalent lightness or density may be obtained, not the exactly identical lightness or density.

In step 7, by solving Neural Network 2 by using the numerical solution from the colorimetric values $L^*a^*b^*$ for the input address values Y, M, C and K of the four-dimensional DLUT color converter 247 and the black addition amount K' for the image output apparatus 300 that has an equivalent lightness to that of the input address value K of the four-dimensional DLUT color converter 247, the remaining image recording signals Y', M', C' and K' for the image output apparatus 300 that are colorimetrically identical to the $L^*a^*b^*$, with black addition amount being K' are obtained. Numerical solution of Neural

Network 2 uses a similar approach to that in the first embodiment.

Next, in step 8, when the input address values Y, M and C of the four-dimensional DLUT color converter 247 are all zero, the image recording signals Y', M', C' and K' obtained in step 7 are all corrected to be zero. In this way, black text and black thin lines specified in a single black color in an electronic manuscript can be reproduced in a single black color that has the same lightness by the image output apparatus 300.

10 This considerably upgrades the reproducibility of black text and black thin lines.

While the image recording signals Y', M', C' and K' are all corrected to be zero in step 8 when the input address values Y, M and C of the four-dimensional DLUT color converter 247 are all zero in this embodiment, step 8 may be skipped when more accuracy in color consistency between input and output is desired.

15

In case the color characteristics of the input color signals Y, M, C and K for printing are close to those of the color signals Y, M, C and K for color printers, reproduction of black text or black thin lines in a single black color may be acceptable visually even when correction of Y', M' and C' in step 8 is skipped.

20

In such a case also, it is possible to skip step 8. Note that it is preferable to perform correction of Y', M' and C'

25

in step 8 as in this embodiment, in order to assure reproduction of black text and black thin lines in a single black color.

Finally, in step 9, by setting the image recording signals Y' , M' , C' and K' obtained in step 8 and the black addition amount K' obtained in step 7 to lattice points of the four-dimensional DLUT color converter 247, it is possible to determine the color conversion parameters of the four-dimensional DLUT color converter 247.

Via the configuration shown in this embodiment, it is possible to perform direct color conversion by using the direct lookup table without configuring the color conversion means 240 by the color conversion processing that has a number of operations, as well as the advantages shown in the first embodiment. This realizes a very fast color conversion. In case hardware is used to realize this embodiment, the embodiment can be realized with hardware easily because of reduced operations.

Next, the third embodiment of the invention will be described. While the third embodiment of the invention is similar to the configuration shown in Fig. 1, like the first embodiment, the configuration of the color conversion means 240 is different. The remaining configuration is the same as that of the first embodiment.

Fig. 6 is a block diagram of the main sections of the second embodiment. In this embodiment, the color conversion

means 240 is configured by a 4-input 3-output DLUT color converter 248 and a one-dimensional LUT gradation converter 249.

5 The 4 -input 3-output DLUT color converter 248 is configured by a four-dimensional direct lookup table that uses the value obtained by dividing each axis of image input color signals Y, M, C and K by 16 as an input address and performs interpolation operation via cubic interpolation to calculate image recording signals Y', M' and C' for the image output
10 apparatus 300.

While the cubic interpolation is applied as an interpolation system for the direct lookup table in this embodiment, other known systems such as the prism interpolation and tetrahedral interpolation may be applied. Number of
15 divisions of each input axis may be other than 16.

While the 4-input 3-output DLUT color converter 248 is configured by a four-dimensional direct lookup table in this embodiment, this is not limiting but any known color conversion system such as the Neural Network may be applied as long as
20 4-input 3-output color conversion is realized.

The one-dimensional LUT gradation converter 249 converts the black addition amount K' for the image output apparatus 300 that has an equivalent lightness to that of the black addition amount K by using the one-dimensional lookup table.
25 In this embodiment, same as the first embodiment, the number

of quantifying divisions of the one-dimensional lookup table is 8 bits. In creating a lookup table, lightness L^* assumed when the screen coverage ratio is changed from 0 to 255 is measured in advance, and the value of the output black addition amount K' that has the lightness equivalent to the lightness L^* of the input black addition amount K is obtained, then set as a lookup table value.

In this embodiment, in order to precisely compensate for the gradation of the input/output black addition amount, one-dimensional lookup table is used for the one-dimensional LUT gradation converter 249. However, any mechanism that can describe the one-dimensional input/output relationship, such as a function formula, is applicable, and the number of quantifying divisions of the lookup table is not limited to 8 bits. Setting can be made so that consistency of density of black addition amount may be obtained between input and output. Conversion characteristics can be specified so that equivalent lightness or density may be obtained, not the exactly identical lightness or density.

In this embodiment, the color conversion means does not limit the input color signals to four color signals Y , M , C and K but color signals containing five or more colors including black may be input. Four color signals used for printing include, for example, HiFiColor containing six colors, that is, four colors Y , M , C and K plus green and orange. Color

signals containing five or more colors can be converted to the image recording signals containing four colors via similar means and method.

For example, in case six color signals are input, black
5 addition signals may be converted by using a one-dimensional lookup table and the six input color signals may be converted to three variable color signals other than black out of the image recording signals by using a 6-input 3-output six-dimensional direct lookup table.

10 By configuring the color conversion means 240 by a 4-input 3-output DLUT color converter 248 and a one-dimensional LUT gradation converter 249 as in this embodiment, compared with the case where the color conversion means 240 is configured by a 4-input 4-output four-dimensional direct lookup table as
15 in the second embodiment, the table memory for the one-dimensional LUT gradation converter 249 is necessary but the number of lattice points in the four-dimensional direct lookup table is reduced to three fourth. Thus it is possible to reduce table memory considerably to realize the color
20 conversion means 240 at a low cost.

Comparing the second embodiment with this embodiment,
1 byte \times 4 = 4 bytes for four colors Y', M', C' and K' is required as lattice point data for each of the input addresses $17 \times 17 \times 17 \times 17 = 83521$, thus the table memory capacity totals 83521
25 $\times 4$ bytes = 33408 bytes in the second embodiment. In this

embodiment, table memory capacity of 83521×3 bytes=249753 bytes is required in the 4-input 3-output DLUT color converter 248 and table memory capacity of 1 byte is required in the one-dimensional LUT gradation converter 249, thus table memory
5 capacity totals 249753 bytes. In this embodiment, the color conversion means 240 can be realized using a very small table memory of approximately three fourth the total in the second embodiment 2.

Fig. 9 shows the steps for determining color conversion
10 parameters for the 4-input 3-output DLUT color converter 248 in this embodiment. In step 1', a patch is output for printed material corresponding to an arbitrary combination of color signals Y, M, C and K for printing input from the manuscript editing apparatus 100. The colorimetric values $L^*a^*b^*$ of the
15 patch are measured via a colorimeter on the market.

Then, the colorimetric values $L^*a^*b^*$ in a field of 2 degrees are measured under the measurement conditions of D50, by using the colorimeter X-Rite 938 from the X-Rite Company. While an arbitrary number of color patches may be used for
20 measurement, it is desirable to use as many patches as possible for a higher-accuracy color conversion model. While the uniform color space $L^*a^*b^*$ color system is used as a color system for measurement in this embodiment, another color system such as the XYZ color system may be used.

25 As a color space and a data set for printing, JapanColor

928 patch colorimetric data standardized in the international standard ISO12842 is used. Other color space and data sets for printing may be used.

In step 2', the Neural Network is instructed to study
5 a data set of plural signals Y, M, C and K and $L^*a^*b^*$ obtained in step 1' as instructor data. In this embodiment, this Neural Network is called Neural Network 1.

While a higher polynomial, conversion table system or Neural Network is generally used for such a color conversion
10 model, the Neural Network is instructed to study a data set comprising a combination of YMCK data and $L^*a^*b^*$ data to model the input color characteristics for printing in this embodiment.

In this embodiment, a Neural Network similar to that in
15 the first embodiment is used and study is performed via the back propagation method. Input color signals are not limited to four color signals Y, M, C and K but color signals containing five or more colors including black may be input.

Next, in step 3', a color patch is output corresponding
20 to an arbitrary combination of image recording signals color signals Y, M, C and K for the image output apparatus 300 is printed out on the image output apparatus 300 and the colorimetric values $L^*a^*b^*$ of the patch are measured via a colorimeter. In this embodiment, a combination of $6 \times 6 \times 6$
25 $\times 6 = 1296$ patches with the screen coverage ratio of each color

being incremented by 20% is printed out as a combination of image recording signals Y' , M' , C' and K' , on the image output apparatus 300. Then, the colorimetric values $L^*a^*b^*$ in a field of 2 degrees are measured under the measurement conditions of
5 D50, by using the colorimeter X-Rite 938 from the X-Rite Company.

While the perceptual uniform color space $L^*a^*b^*$ color system is used as a color system for measurement in this embodiment, another color system such as the XYZ color system
10 may be used. Note that a perceptual uniform color space is preferable in order to evaluate the color difference in solving the color conversion model.

In step 4', the Neural Network is instructed to study a data set of plural signals Y' , M' , C' and K' and $L^*a^*b^*$
15 obtained as instructor data. In this embodiment, this Neural Network is called Neural Network 2. In this embodiment, a Neural Network similar to that in the first embodiment is used and study is performed via the back propagation method.

In step 5', colorimetric values $L^*a^*b^*$ for the input
20 address values Y , M , C and K of the 4-input 3-output DLUT color converter 248 are determined by using the Neural Network obtained in step 2'.

Next, in step 6', the one-dimensional lookup table is used to determine black addition amount K' for the image output
25 apparatus 300 that has an equivalent lightness to that of the

input address value K of the 4-input 3-output DLUT color converter 248. In this embodiment, same as the first embodiment, the number of quantifying divisions of the one-dimensional lookup table is 8 bits. In creating a lookup
5 table, lightness L^* assumed when the screen coverage ratio is changed from 0 to 255 is measured in advance, and the value of the output black addition amount K' that has the lightness equivalent to the lightness L^* of the input black addition amount K is obtained, then set as a lookup table value.

10 In this embodiment, same as the first embodiment, the number of quantifying divisions of the one-dimensional lookup table is 8 bits. In creating a lookup table, lightness L^* assumed when the screen coverage ratio is changed from 0 to 255 is measured in advance, and the value of the output black
15 addition amount K' that has the lightness equivalent to the lightness L^* of the input black addition amount K is obtained, then set as a lookup table value.

In this embodiment, in order to precisely compensate for the gradation of the input/output black addition amount,
20 one-dimensional lookup table is used in step 6'. However, any mechanism that can describe the one-dimensional input/output relationship, such as a function formula, is applicable, and the number of quantifying divisions of the lookup table is not limited to 8 bits.

25 Setting can be made so that consistency of density of

black addition amount may be obtained between input and output. Conversion characteristics can be specified so that equivalent lightness or density may be obtained, not the exactly identical lightness or density.

- 5 In step 7', by solving Neural Network 2 by using the numerical solution from the colorimetric values $L^*a^*b^*$ for the input address values Y, M, C and K of the 4-input 3-output DLUT color converter 248 and the black addition amount for the image output apparatus 300 that has an equivalent lightness to that
- 10 of the input address value K of the 4-input 3-output DLUT color converter 248, the remaining image recording signals Y', M', C' and K' for the image output apparatus 300 that are colorimetrically identical to the $L^*a^*b^*$, with black addition amount being K' are obtained. Numerical solution of Neural
- 15 Network 2 uses a similar approach to that in the first embodiment.

- Next, in step 8', When the input address values Y, M and C of the 4-input 3-output DLUT color converter 248 are all zero, the image recording signal Y', M', C' and K' obtained in step
- 20 7' are all corrected to be zero. In this way, black text and black thin lines specified in a single black color in an electronic manuscript can be reproduced in a single black color that has the same lightness by the image output apparatus 300. This considerably upgrades the reproducibility of black text
- 25 and black thin lines.

While the image recording signals Y', M', C' and K' are all corrected to be zero in step 8' when the input address values Y, M and C of the 4-input 3-output DLUT color converter 248 are all zero in this embodiment, step 8' may be skipped when
5 more accuracy in color consistency between input and output is desired.

In case the color characteristics of the input color signals Y, M, C and K for printing are close to those of the color signals Y, M, C and K for color printers, reproduction
10 of black text or black thin lines in a single black color may be acceptable visually even when correction of Y', M' and C' in step 8' is skipped.

In such a case also, it is possible to skip step 8'. Note that it is preferable to perform correction of Y', M' and C'
15 in step 8' as in this embodiment, in order to assure reproduction of black text and black thin lines in a single black color.

Finally, in step 9', by setting the image recording signals Y', M', C' and K' obtained in step 8' and the black
20 addition amount K' obtained in step 7 to lattice points of the 4-input 3-output DLUT color converter 248, it is possible to determine the color conversion parameters of the 4-input 3-output DLUT color converter 248.

Via the configuration shown in this embodiment, it is
25 possible to perform direct color conversion by using a 4-input

3-output four-dimensional direct lookup table and a one-dimensional lookup table without configuring the color conversion means 240 by the color conversion processing that has a number of operations, as well as the advantages shown

5 in the first and second embodiments. This realizes a very fast color conversion at a low cost by using a very small table memory capacity. In case hardware is used to realize this embodiment, the embodiment can be realized with hardware at a low cost because of a very small table memory capacity.

10 As mentioned earlier, device-independent color signals in the color system color space are obtained from input color signals containing five more colors including black. An output black color signal is determined that has the lightness equivalent to the lightness of the input black color signal

15 K. From the output black color signal and the device-independent color signals, the remaining three variable color signals are determined by solving the color conversion model for the image output apparatus 300 by using the numerical solution, so that colorimetric consistency between the

20 remaining three variable color signals and the device-independent color signals may be obtained. When color signals other than the input black color signal are all zero, the remaining three variable color signals are corrected to be zero. In this way, both the high color consistency between input and

25 output and favorable reproduction in a single black color of

black text and black thin lines specified in a single black color in an electronic manuscript, with a consistent lightness, are realized.

According to the invention, it is possible to realizes
5 a very fast color conversion by using the 4-or-more-input
4-output direct lookup table without configuring the color
conversion means by the color conversion processing that has
a number of operations. In case hardware is used to realize
this embodiment, the embodiment can be realized with hardware
10 easily because of reduced operations.

According to the invention, it is possible to realizes
a very fast color conversion by using the 4-or-more-input
3-output direct lookup table without configuring the color
conversion means by the color conversion processing that has
15 a number of operations. This realizes a very fast color
conversion at a low cost by using a very small table memory
capacity. In case hardware is used to realize this embodiment,
the embodiment can be realized with hardware at a low cost
because of a very small table memory capacity.

20

WHAT IS CLAIMED IS:

1. A color image processing method for converting first color signals containing four or more variables including black to second color signals containing four variables including
5 black, said method comprising the steps of:
 obtaining device-independent color signals on color system color coordinates from said first color signals,
 determining a black color signal in said second color signals having the identical or virtually identical density
10 as the black color signal in said first color signals, and
 determining the remaining three variable color signals in said second color signals from the black color signal and the device-independent color signals in said second color signals so that colorimetric consistency of the three variable
15 color signals may be obtained.
2. The color image processing method according to claim 1, further comprising the step of:
 setting the color signals other than black in said second
20 color signals to zero, in case the color signals other than black in said first color signals are zero.
3. The color image processing method according to claim 1, wherein
25 the color signals other than black in said first color

signals and in said second color signals are yellow, magenta, and cyan.

4. The color image processing method according to claim 1,
5 wherein

the device-independent color signals on said color system color coordinates are L*a*b color signals.

5. The color image processing method according to claim 1,
10 wherein

the step for determining a black color signal in said second color signals having the identical or virtually identical density as the black color signal in said first color signals is configured by a lookup table.

15
6. The color image processing method according to claim 1, wherein

a function showing the relationship between said second color signals and the device-independent color signals on color system color coordinates is obtained in advance via a step for
20 determining the remaining three variable color signals in said second color signals from the black color signal and the device-dependent color signals in said second signals so that colorimetric consistency of the three variable color signals
25 may be obtained, and

said function is solved by using as an input the black color signal and the device-dependent color signals in said second signals, in order to determine the remaining three variable color signals in said second color signals.

5

7. A color image processor for converting first color signals containing four or more variables including black to second color signals containing four variables including black, said processor comprising:

10 means for obtaining device-independent color signals on color system color coordinates from said first color signals,

means for determining a black color signal in said second color signals having the identical or virtually identical density as the black color signal in said first color signals,

15 and

means for determining the remaining three variable color signals in said second color signals from the black color signal and the device-independent color signals in said second color signals so that colorimetric consistency of the three variable color signals may be obtained.

20

8. The color image processor according to claim 7, wherein said color image processor comprises means for setting the color signals other than black in said second color signals to zero, in case the color signals other than black in said

25

first color signals are zero.

9. The color image processor according to claim 7, wherein
the color signals other than black in said first color
5 signals and in said second color signals are yellow, magenta,
and cyan.

10. The color image processor according to claim 7, wherein
the device-independent color signals on said color
10 system color coordinates are L^*a^*b color signals.

11. The color image processor according to claim 7, wherein
the step for determining a black color signal in said
second color signals having the identical or virtually
15 identical density as the black color signal in said first color
signals is configured by a lookup table.

12. The color image processor according to claim 7, wherein
a function showing the relationship between said second
20 color signals and the device-independent color signals on color
system color coordinates is obtained in advance via means for
determining the remaining three variable color signals in said
second color signals from the black color signal and the
device-dependent color signals in said second signals so that
25 colorimetric consistency of the three variable color signals

may be obtained, and

said function is solved by using as an input the black color signal and the device-dependent color signals in said second signals, in order to determine the remaining three
5 variable color signals in said second color signals.

13. The color image processor, wherein
each means of said color image processor according to claim 7 is configured by a 4-or-more-input 4-output color
10 converter that inputs color signals containing four or more variables in said first color signals and outputs four variable color signals in said second color signals.

14. The color image processor according to claim 13, wherein
15 said 4-or-more-input 4-output color converter is configured by a direct lookup table.

15. The color image processor comprising:
each means of the color image processor according to
20 claim 7 is configured by
a 4-or-more-input 3-output color converter that inputs color signals containing four or more variables in said first color signals and outputs three variable color signals other than black out of the four variable color signals in said second
25 color signals, and

a 1-input 1-output color converter that inputs the black color signal in said first color signals and outputs the black color signal in said second color signals.

- 5 16. The color image processor according to claim 15, wherein
said 4-or-more-input 3-output color converter is
configured by a direct lookup table, and
said 1-input 1-output color converter is configured by
a lookup table.

10

ABSTRACT OF THE DISCLOSURE

The invention comprises a device-independent color space converter 241 that obtains device-dependent color signals on the on the color system color coordinates from first color
5 signals, a gradation compensator 242 that determines a black color signal in the second color signals having the identical or virtually identical density as the black color signal in the first color signals, and a YMC decision section 243 that
10 determines the remaining three variable color signals in the second color signals from the black color signal and the device-independent color signals in the second color signals so that colorimetric consistency of the three variable color signals may be obtained.

[Fig. 1]

100: Manuscript editing apparatus

200: Image processor

210: Editing apparatus communication means

5 220: Format conversion means

230: Rasterizing means

240: Color conversion means

250: Output apparatus communication means


300: Image output apparatus

10

【書類名】 図面


【図 1】

Fig. 1



【図2】

Fig. 2



[Fig. 3]

220: Format conversion means

230: Rasterizing means

240: Color conversion means

5 241: Device-independent color space converter

242: Gradation compensator

243: YMC decision section

244: YMC judgment section

245: YMC correction section

10 246: YMCK output section


250: Output apparatus communication means

[Fig. 4]

15 Output black addition amount

Input black addition amount

【図 3】 Fig. 3




【図4】

Fig. 4

Output black addition amount

出力黒量



入力黒量

Input black addition amount

[Fig. 5]

- #1 Comparison of color conversion accuracy between the present invention and related art
- #2 Present invention
- 5 #3 Japanese Patent Laid-Open No. 87343/1995
- #4 Japanese Patent Laid-Open No. 65534/1996
- #5 Japanese Patent Laid-Open No. 116456/1996
- #6 Japanese Patent Laid-Open No. 186894/1997
- #7 Average color difference
- 10 #8 Maximum color difference
- #9 Comparison of reproduction in a single black color between the present invention and related art
- #10 Color conversion system
- #11 Reproduction in a single black color
- 15 #12 Legend:
 - : Reproduction in a single black color possible
 - ×: Reproduction in a single black color impossible


20 [Fig. 6]

- 220: Format conversion means
- 230: Rasterizing means
- 240: Color conversion means
- 247: Four-dimensional DLUT color converter
- 25 250: Output apparatus communication means

〔図 5〕

Fig. 5

本発明と従来技術の色変換精度比較



本発明と従来技術の墨1色再現比較

色変換方式	本発明	特開平7-87343	特開平8-65534	特開平8-116456	特開平9-186894
墨1色再現	○	×	○	○	×


判例

○ 墨1色再現可能

× 墨1色再現不可能

【図 6】

Fig. 6



[Fig. 7]

Step 1

A color patch is printed out corresponding to an arbitrary combination of printing color signals Y, M, C and K and the colorimetric values color signals Y, M, C and K are measured.

Step 2

Neural Network 1 is instructed to study a data set of Y, M, C and K and $L^*a^*b^*$ as instructor data.

10

Step 3

A color patch corresponding to an arbitrary combination of image recording signals Y', M', C' and K' for the image output apparatus 300 is printed out and the colorimetric values $L^*a^*b^*$ are measured.

15

Step 4

Neural Network 2 is instructed to study a data set of Y', M', C' and K' and $L^*a^*b^*$ as instructor data.

20

Step 5

Colorimetric values $L^*a^*b^*$ for the input address values Y, M, C and K of the four-dimensional DLUT color converter are determined by using Neural Network 1.

25

Step 6

Black addition amount K' for the image output apparatus that has an equivalent lightness to that of the input address value K of the four-dimensional DLUT color converter is determined
5 by using the one-dimensional lookup table.

Step 7

By solving Neural Network 2 by using the numerical solution from the colorimetric values $L^*a^*b^*$ and the black addition
10 amount K' , colorimetrically consistent values Y' , M' and C' are calculated.


Step 8

When the input address values Y , M and C of the four-dimensional
15 DLUT color converter are all zero, calculated values Y' , M' and C' are all corrected to be zero.

Step 9

Obtained Y' , M' and C' and black addition amount K' are set
20 to lattice points of the four-dimensional DLUT color converter.


【図7】 Fig. 7



[Fig. 8]

- 220: Format conversion means
- 230: Rasterizing means
- 240: Color conversion means
- 5 248: Four-dimensional 3-output DLUT color converter
- 249: One-dimensional LUT gradation converter
- 250: Output apparatus communication means

【図8】 Fig. 8



[Fig. 9]

Step 1'

A color patch is printed out corresponding to an arbitrary combination of printing color signals Y, M, C and K and the
5 colorimetric values color signals Y, M, C and K are measured.

Step 2'

Neural Network 1 is instructed to study a data set of Y, M, C and K and $L^*a^*b^*$ as instructor data.

10

Step 3'

A color patch corresponding to an arbitrary combination of image recording signals Y', M', C' and K' for the image output apparatus 300 is printed out and the colorimetric values
15 $L^*a^*b^*$ are measured.

Step 4'

Neural Network 2 is instructed to study a data set of Y', M', C' and K' and $L^*a^*b^*$ as instructor data.

20

Step 5'

Colorimetric values $L^*a^*b^*$ for the input address values Y, M, C and K of the 4-input 3-output DLUT color converter are determined by using Neural Network 1.

25

Step 6'

Black addition amount K' for the image output apparatus that has an equivalent lightness to that of the input address value K of the four-dimensional DLUT color converter is determined
5 by using the one-dimensional lookup table.

Step 7'

By solving Neural Network 2 by using the numerical solution from the colorimetric values $L^*a^*b^*$ and the black addition
10 amount K' , colorimetrically consistent values Y' , M' and C' are calculated.

Step 8'

When the input address values Y , M and C of the 4-input 3-
15 output DLUT color converter are all zero, calculated values Y' , M' and C' are all corrected to be zero.

Step 9'

Obtained Y' , M' and C' and black addition amount K' are set
20 to lattice points of the four-dimensional DLUT color converter.

+ 図 9 + F 9 9

Step1'

印刷色信号YMCKの任意の組み合わせに対する色パッチをプリントアウトし、測色値 $L^*a^*b^*$ を測定する。



Step2'

YMCKと $L^*a^*b^*$ のデータセットを教師データとしてニューラルネットワーク1に学習させる。



Step3'

画像記録信号Y'M'C'K'の任意の組み合わせに対する色パッチをプリントアウトし、測色値 $L^*a^*b^*$ を測定する。



Step4'

Y'M'C'K'と $L^*a^*b^*$ のデータセットを教師データとしてニューラルネットワーク2に学習させる。



Step5'

4入力3出力DLUT色変換器の入力アドレス値YMCKに対する測色値 $L^*a^*b^*$ をニューラルネットワーク1により決定する。



Step6'

4入力3出力DLUT色変換器の入力アドレス値Kと等価な明度になる画像出力装置の墨量K'を1次元のルックアップテーブルにより決定する。



Step7'

$L^*a^*b^*$ と墨量K'からニューラルネットワーク2を数値解法で解くことにより、測色的に一致するY'M'C'の値を算出する。



Step8'

4入力3出力DLUT色変換器の入力アドレス値YMCが同時に零の場合に、算出されたY'M'C'の値をすべて零に修正する。



Step9'

得られたY'M'C'と墨量K'を4入力3出力DLUT色変換器の格子点に設定する。

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

U.S. DEPARTMENT OF COMMERCE
Patent and Trademark Office

ATTORNEY DOCKET NO.:

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

A COLOR IMAGE PROCESSING METHOD AND A COLOR IMAGE PROCESSOR

the specification of which:

is attached hereto; or

was filed as United States application Serial No. _____ on _____ and was amended on _____ (if applicable); or

was filed as PCT international application Number _____ on _____ and was amended under PCT Article 19 on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office information which is material to the patentability of claims presented in this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate or §365(a) of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

PRIOR FOREIGN APPLICATION(S):

COUNTRY (if PCT, indicate PCT)	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED
Japan	P. Hei. 11-353936	14/ 12/ 1999	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No

Combined Declaration For Patent Application and Power of Attorney - (Continued)
(includes Reference to PCT International Applications)

ATTORNEY DOCKET NO.:

I hereby claim the benefits under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

U.S. PROVISIONAL APPLICATIONS

U.S. PROVISIONAL APPLICATION NO.

U.S. FILING DATE

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or §365(c) of any PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to the patentability of claims presented in this application in accordance with Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT:

U.S. APPLICATIONS

STATUS (Check One)

U.S. APPLICATION NO.

U.S. FILING DATE

PATENTED

PENDING

ABANDONED

POWER OF ATTORNEY: As a named inventor, I hereby appoint the registered practitioners of Morgan, Lewis & Bockius LLP included in the Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to that Customer Number.

Customer Number: 009629

Direct Telephone Calls To:
(name and telephone number)

Robert J. Gaybrick
202-467-7501

Combined Declaration For Patent Application and Power of Attorney - (Continued)
(includes Reference to PCT International Applications)

ATTORNEY DOCKET NO.:

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

FULL NAME OF SOLE OR FIRST INVENTOR	Masahiko KUBO		
RESIDENCE & CITIZENSHIP	Kanagawa Japan		COUNTRY OF CITIZENSHIP Japan
POST OFFICE ADDRESS	c/o Fuji Xerox Co., Ltd., 430, Sakai, Nakai-machi, Ashigarakami-gun, Kanagawa, Japan		
FIRST OR SOLE INVENTOR'S SIGNATURE	<i>Masahiko Kubo</i>		DATE November 20, 2000
FULL NAME OF SECOND INVENTOR			
RESIDENCE & CITIZENSHIP			COUNTRY OF CITIZENSHIP
POST OFFICE ADDRESS			
SECOND INVENTOR'S SIGNATURE			DATE
FULL NAME OF THIRD INVENTOR			
RESIDENCE & CITIZENSHIP			COUNTRY OF CITIZENSHIP
POST OFFICE ADDRESS			
THIRD INVENTOR'S SIGNATURE			DATE

Listing of Inventors Continued on attached page(s) [] Yes [x] No